



(11) **EP 1 352 844 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**15.10.2003 Bulletin 2003/42**

(51) Int Cl.7: **B65D 51/30, B65D 81/26,  
B65D 43/16**

(21) Application number: **03252334.2**

(22) Date of filing: **11.04.2003**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
HU IE IT LI LU MC NL PT RO SE SI SK TR**  
Designated Extension States:  
**AL LT LV MK**

(72) Inventors:  
• **Belfance, John**  
**Fonda, New York 12068 (US)**  
• **Supranowicz, Ronald**  
**Lenox, Massachusetts 01240 (US)**

(30) Priority: **11.04.2002 US 372339 P**  
**15.08.2002 US 319570**


(74) Representative: **Stevens, Ian Edward**  
**Eric Potter Clarkson,**  
**Park View House,**  
**58 The Ropewalk**  
**Nottingham NG1 5DD (GB)**

(71) Applicant: **Csp Technologies, Inc.**  
**Auburn, AL 36832 (US)**

(54) **Desiccant vial assembly for effervescent tablets**

(57) The present invention is directed to a one-piece vial assembly (1) having a container (10) and cap (30) that provides a substantially moisture-free environment for effervescent tablets, and other items that require packaging and retention in a substantially moisture-free environment. In one embodiment, the container and cap are joined together by a hinge (34); hence the vial assembly is a one-piece assembly in which the cap is opened and closed in a "flip-top" arrangement. The vial assembly of the present invention includes a desiccant

entrained plastic. In one embodiment, the desiccant entrained plastic is located in a desiccant sleeve, which surrounds at least a portion of the product within the vial assembly sleeve. In yet another embodiment, the sleeve surrounds the vial assembly interior with a thin-walled plastic so that the product contained within the vial assembly is completely surrounded by the desiccant entrained plastic sleeve. In another embodiment, the items contained in the vial assembly of the present invention are subjected to about fifty times less moisture when compared to a conventional stoppered vial.



**EP 1 352 844 A1**

## Description

### RELATED APPLICATION

[0001] This is a continuation-in-part of application 60/372,339 filed April 11, 2002.

### FIELD OF THE INVENTION

[0002] The present application relates to a desiccant entrained plastic vial assembly for packaging and retaining effervescent tablets, which should be maintained in a substantially moisture-free environment until used by the end user. The present application also discloses methods for using the desiccant entrained plastic vial assembly.

### BACKGROUND OF THE INVENTION

[0003] Effervescent tablets have been used to deliver drugs, vitamins and nutritional supplements, among other things (e.g. denture cleaners). These tablets quickly dissolve in water and are consumed in liquid form. In an attempt to keep the tablet environment moisture free, one method that is conventionally used are packaging the tablets in rigid two-piece containers with a stoppered cap. The container typically contains a sachet of silica gel desiccant to absorb moisture in the container over the shelf life. For highly moisture sensitive products, the tablets may be wrapped in foil, and additionally, may be placed in an aluminum container with a desiccant stopper cap. In another example, the effervescent tablets are packaged in foil/paper laminate packets.

[0004] It is desirable to provide a one-piece vial assembly having a container and cap that can provide a relatively moisture free environment for effervescent tablets, and other items that require packaging and retention in a relatively moisture free environment. It is also desirable to provide a one-piece vial assembly that is easier to open than existing containers and packaging. It is also desirable to provide packaging for effervescent containers that are relatively less voluminous when compared to packaging options that are currently available.

### SUMMARY OF THE INVENTION

[0005] The present invention is directed to a interconnected vial assembly having a container and cap that provides a substantially moisture-free environment for effervescent tablets, beverage-forming tablets, and other items that require packaging and retention in a substantially moisture-free environment. In one embodiment, the container and cap are joined together by a hinge; hence, in this embodiment, the vial assembly is an interconnected assembly in which the cap is opened and closed in a "flip-top" arrangement. In another em-

bodiment, the hinge is integral with the cap and container, which provides a one-piece vial assembly. The vial assembly of the present invention includes a desiccant entrained plastic. In one embodiment, the desiccant entrained plastic is located in a desiccant sleeve, which surrounds at least a portion of the product within the vial assembly sleeve. In yet another embodiment, the sleeve surrounds the vial assembly interior with a thin-walled plastic so that the product contained within the vial assembly is completely surrounded by the desiccant entrained plastic sleeve. In another embodiment, the items contained in the vial assembly of the present invention are subjected to about fifty times less moisture when compared to a conventional stoppered vial.

[0006] In a further embodiment, the vial assembly of the present invention can store a number of effervescent tablets, for example, 5 to 40 effervescent tablets, ranging in size from about 7 mm to about 36 mm in diameter and from about 6.2 mm to about 7.8 mm in thickness. In a further embodiment, the vial is dimensioned and sized to store 10 or 20 tablets having a size of about 25mm in diameter and about 7 mm in thickness.

[0007] In yet another embodiment, the vial assembly contains a spring joined to the inner wall of the cap. The spring cushions the tablets. In another embodiment, the desiccant is positioned within the spring. In yet another embodiment, the structure of the spring retains a sachet containing a desiccant material. In yet another embodiment, the desiccant is positioned to surround the interior of the vial assembly and in the spring joined to the inner wall of the cap.

[0008] In yet another embodiment, a cushioning spring is positioned in the bottom of the container.

[0009] In another embodiment of the present invention, desiccant is located at the bottom of the container. In yet another embodiment, the desiccant located in the bottom of the container is positioned within a spring at the bottom of the container. In one embodiment, the desiccant is entrained within the plastic material that constructs the spring. In yet another embodiment, a sachet of desiccant is retained in the spring. In yet another embodiment, a false bottom or platform is provided at the bottom of the container, in which a desiccant entrained plastic is employed in the construction of these components. In yet another embodiment, a sachet of desiccant is retained by the false bottom or platform.

[0010] In yet further embodiments, combinations of the above possibilities are employed for locating a desiccant material within the container.

[0011] The vial assembly of the present invention may optionally include tamper-evident features and child resistant features. Other features may be included in the vial assemblies of the present invention and are discussed in "Detailed Description" section of this disclosure. These features are disclosed in pending U.S. patent application no. 09/710,330, filed November 11, 2000, incorporated herein by reference.

[0012] In one embodiment, the container has an up-

per portion and an outer surface. The container has a rim at the upper portion. The upper portion of the container includes a flexible and detachable protrusion having a contact element and a break point. In another embodiment, the cap has a base with an outer periphery and a skirt extending perpendicularly and outwardly around the outer periphery of the base. The cap also has a hinge and a tab extending perpendicularly and outwardly from the skirt of the cap. In still another embodiment, the top has a least two slots capable of housing the protrusion. In yet another embodiment, the tab has a first slot and a second slot including an interlocking device for engaging with the protrusion.

[0013] In a further embodiment, when the container is in an empty state, the protrusion is positioned within the first slot. In still a further embodiment, when the container is in a filled stage, the cap is placed upon the container and the protrusion is repositioned within the second slot causing the contact element of the protrusion to engage the interlocking device of the second slot and thus to form a tamper-proof seal. For purposes of this invention, the term "empty stage" refers to a stage when the container is empty prior to filling, such as when the container is shipped by the manufacturer of the container to the site where items are placed inside the container. The term "filling stage" refers to a stage after the container has been filled with its content. In one embodiment, the contents may include effervescent tablets.

[0014] In yet another embodiment, the protrusion is formed in such a way that, if the cap is opened (i.e. tampered with), the protrusion will break off and thus, evidence of tampering with the container will be evident by the broken protrusion. It will be appreciated that it may not be possible to replace the protrusion once it has broken, since the protrusion is formed integrally with the container. Therefore, it should not be possible to defeat the tamper-proof capabilities by replacing the original broken protrusion. It will also be appreciated that the interlocked protrusion not only provides tamper-proof function, but also may aid in preventing dislodgement of the cap during transport.

[0015] For purposes of the present invention, the phrase "tamper-proof seal" means a visual indication that: (a) when not broken, the container's cap has not been opened; and (b) when broken, the container cap has been opened and thus, visually displays that the container was tampered with.

[0016] In another embodiment, the present invention relates to a method of tamper-proofing a container and a cap assembly by: (a) providing a container have an upper portion and an outer surface, the upper portion having a flexible and a detachable protrusion having a contact element and a break point; and a cap having a base with an outer periphery and a skirt extending perpendicularly and outwardly around the outer periphery of the base, the cap has a hinge and a tab extending perpendicularly and outwardly from the skirt of the cap, the tab comprising a first and second slot capable of

housing the protrusion, the second slot having an interlocking device; (b) positioning the protrusion within the first slot in an empty stage; (c) opening the cap and filling the container; and (d) closing the cap upon the container and repositioning the protrusion within the second slot thereby allowing the contact element of the protrusion to engage the interlocking device to form a tamper-proof seal.

[0017] In yet another embodiment, the method further comprises applying a sufficient frontal, upward force upon the tab to allow the interlocking device of the slot to engage the contact element of the protrusion and thus to detach the protrusion from the flange at the break point to thereby breach the seal.

#### BRIEF DESCRIPTION OF DRAWINGS

[0018] A more complete appreciation of the present invention and many of the attendant advantages thereof will be readily understood by reference to the following description was considered in connection with the accompanying drawings in which:

FIGURE 1 is a longitudinal sectional view of one embodiment of the vial assembly of the present invention;

FIGURE 2 is an overhead plan view of one embodiment of the vial assembly in an opened position;

FIGURE 3 is a side elevation view of one embodiment of the present invention of the vial assembly in an empty stage;

FIGURE 4 is a side elevation view of one embodiment of the present invention of the vial assembly in a filled stage;

FIGURE 5 is a blow-up of one embodiment of the present invention of the protrusion of the flange of the container in the empty stage; and

FIGURE 6 is a blow-up of one embodiment of the present invention of the protrusion of the flange of the container in the filled stage.

FIGURE 7 is a side elevation view of another embodiment of the present invention of the vial assembly;

FIGURE 8 is a side elevation view of another embodiment of the present invention of the vial assembly;

FIGURE 9 is a side elevation view of another embodiment of the present invention of the vial assembly;

FIGURE 10 is a side elevation view of another embodiment of the present invention of the vial assembly;

FIGURE 11 is a side elevation view of another embodiment of the present invention of the vial assembly; and

FIGURE 12 is a view along line A-A, as shown in Figure 11.

FIGURE 13 is a cross sectional view of another em-

bodiment of the present invention.

**[0019]** Among those benefits and improvements that have been disclosed, other objects and advantages of this invention will become apparent from the following description taken in conjunction with the accompanying drawings. The drawings constitute a part of this specification and include exemplary embodiments of the present invention and illustrate various embodiments and features thereof.

#### DETAILED DESCRIPTION OF THE PRESENT INVENTION

**[0020]** Referring now to the drawings wherein like references designate identical or corresponding parts throughout the several views, and more particularly to FIG. 1 wherein one embodiment of the one-piece vial assembly 1 of the present invention is illustrated. The assembly 1 comprises a container 10 having a base 16, or internal cavity 15, and outer surface 12 and an upper portion 11. Container 10 has an inner sleeve 17 constructed of desiccant-entrained plastic 17. The container 10 has a rim 13 at the upper portion 11. The container 10 also has a flange 14 extending radially outwardly from the outer surface 12 of the container 10. A detachable protrusion 20 with a contact element 21 and a break point 22 is located at or near flange 14. The assembly 1 also includes a cap 30 having a base 31. The cap 30 also has a tab 40 and a hinge 34. The tab 40 has a first and second slot 41 and 42 respectively, capable of housing the protrusion 20. The second slot 42 comprises an interlocking device 43.

**[0021]** The hinge 34 is also attached at or near the container flange 14. In one embodiment, the hinge 34 has a recess 35 that function as a binding point for ease of opening and closing of the container 10. While the figures depict the hinge 34 as integral with the cap 30 and container 10, the skilled artisan would readily appreciate that any kind of hinge may be employed, such as a hinge constructed of a plurality of components. For example, to name just one possibility, an arrangement can be provided where a hinge component of the cap is engaged with a hinge component of the container.

**[0022]** The base 31 of the cap 30 has an inner surface 36 and an outer surface 37. A spring element 38 is joined to the inner surface 36 of the base 31 of the cap 30. The spring element 38 is constructed of helical strands 39. In one embodiment, some of the helical paths extend clockwise, and/or others extend counterclockwise, so that the helical strands either intersect or do not intersect. The helical strands 39 are joined at a distal spring end 44 to a ring 45. Preferably, the spring element 38, that is, the helical strands 39 and the ring 45, is unitary in its construction.

**[0023]** In one embodiment of the present invention, the desiccant material is present only in the spring element. In yet another embodiment, the desiccant mate-

rial is present only in the sidewalls of the container. In yet another embodiment, the desiccant material is present in both the spring element and the sidewalls of the container. In yet another embodiment, a desiccant-containing sachet is retained within the spring element 38.

**[0024]** Suitable material for vial assembly 1 includes plastic (e.g. thermoplastic, such as polypropylene and polyethylene). In an embodiment, the cap 30 (including spring element 38) and the container 10 may be integrally molded of the plastic to form a hinge 34 therebetween. In another embodiment, the cap 30 and the container 10 may be produced in a conventional molding process and, in still another embodiment, may be molded in accordance with the mold similar to that disclosed in U.S. Patent Nos. 4,783,056 and 4,812,116 respectively. In a further embodiment, with such a process and mold, the assembly, including the cap, container, spring, and hinge may be produced in accordance with the operation disclosed in U.S. Patent Nos. 4,783,056 and 4,812,116 or, in another embodiment, may be produced in accordance with U.S. Patent No. 5,723,085 or 6,303,064. The disclosure of these patents are incorporated by reference herein.

**[0025]** FIG. 2 refers to an overhead plan view of the assembly 10 of the present invention in an opened position of one embodiment of the present invention. The assembly 10 includes the container 10 and the cap 30 connected by the hinge 34. The container 10 has the cavity 15, the rim 13 and the flange 14. The cap 30 includes the circular base 31 and the tab 40. The tab 40 includes a first slot 41 and second slot 42. The hinge 34 has a recess 35 and two elements, 137 and 138 respectively. The first element 137 is attached to the flange 14 of the container 10 and second element 138 is attached to the cap 30.

**[0026]** FIG. 3 and FIG. 5 depict yet another embodiment of the present invention of the container and cap assembly 1 in the empty stage prior to filling with effervescent tablets or other items that should be packaged and stored in a substantially moisture-free environment. In one embodiment, the container 10 has a flange 14 which includes protrusion 20. In another embodiment, protrusion 20 is attached directly to container 10. The protrusion 20 has a u-shaped element 25. The protrusion 20 has a contact element 21 and a break point 22. In the empty stage, the contact element 21 of the protrusion 20 is situated in the first slot 41 of the top 40 of the cap 30. It is understood that other designs of first slot 41 are contemplated. The only design requirement of first slot 41 is that it serves the purpose of holding protrusion 20 in place during handling and prior to the filling stage. As such, protrusion 20 is protected from accidentally being torn off prior to engaging protrusion 20 with interlocking device 43. There is a space between the protrusion 20 and the stop rib 26 and the second slot 42 with the interlocking device 43 remaining empty.

**[0027]** FIG 4 and FIG 6 illustrate the vial assembly 1

of the present invention of an embodiment after it has been filled. The cap 30 is placed upon the container 10 and the protrusion 20 is repositioned with the second slot 42. The contact element 21 of the protrusion 20 engages the interlocking device 43 of the second slot 42 of the tab 40 to form a tamper-proof seal. The stop rib 26 restricts the movement of the protrusion 20.

**[0028]** Subsequently, in operation, a user would break the tamper-proof seal by applying sufficient frontal upward force to allow the interlocking device 43 of the second slot 42 to engage the contact element 21 of the protrusion 20 to detach the protrusion 20 from the flange 14 at the break point 22.

**[0029]** It is understood that the design of break point 22 is such that, when sufficient frontal upward force is applied to the cap to open the vial assembly, the protrusion must fail (e.g. break) at break point 22 prior to any failure between the engagement of protrusion 20 with interlocking device 43. Consequently, in one embodiment, break point 22 width is sufficiently narrow to break when sufficient frontal upward force is applied to open the vial assembly while, at the same time, is sufficiently flexible and of suitable design to allow for: (a) protrusion 20 to be moved from the first slot to the second slot without breakage; and (b) protrusion 20 to remain engaged with interlocking device 43 while sufficient force is applied to open the vial assembly and break at break point 22.

**[0030]** Interlocking device 43 may be any design that is able to directly mate with protrusion 20 and remain engaged even when sufficient frontal force is applied to cause a break at break point 22. Such interlocking devices may include teeth, flexible projections and suitable wedge-like shapes.

**[0031]** Figure 7 shows an embodiment where springs 38, 38', are positioned on the inner side of the cap 30 and on the base 16 of the container 10. Spring 38' is can be structured in the same way as spring 38. The springs can be constructed of a desiccant-entrained plastic, or they may retain a desiccant-containing sachet, and combinations of these arrangements may also be provided. One of the springs may also be provided merely for cushioning the contents of the vial, to prevent breakage of the contents.

**[0032]** The bottom spring 38' may be placed in the bottom of the vial during the second part of a two-shot injection molding operation. The height adjustment is controlled by the spring length prior to compression and the end compressed height based on the number and weight of the tablets and the thickness of the strands 39.

**[0033]** Figure 8 depicts an arrangement similar to Figure 7. However, here the bottom spring 38' is molded in a separate process. The spring is then loaded into the vial via mechanical means, such as loaded by a robot, prior to closing the cap. The spring 38' may be loaded in a post molding step, but this would require reopening the vial. The process could be fully automated, or ac-

complished manually. The springs can be constructed of a desiccant-entrained plastic, or they may retain a desiccant-containing sachet, and combinations of these arrangements may also be provided. One of the springs may also be provided merely for cushioning the contents of the vial, to prevent breakage of the contents.

**[0034]** In Figure 9, springs are positioned on the base 16 and cap 30 of the container 10. Here, an overmolding process is employed. A tube of desiccant is placed on the tall core of the mold, leaving the end of the core uncovered. The spring molding mechanism resides in the center of the tall core and these components are variable to create different spring lengths and helix web thicknesses for different tablet stack heights and weights. The springs can be constructed of a desiccant-entrained plastic, or they may retain a desiccant-containing sachet, and combinations of these arrangements may also be provided. One of the springs may also be provided merely for cushioning the contents of the vial, to prevent breakage of the contents.

**[0035]** Figure 10 shows yet another embodiment where an inner wall is positioned on the inside of the container. The inner wall reduces the inside diameter of the container, with the top of the inner wall providing a ledge on which the tablets or other item stored in the container can rest. The height of the ledge can be varied to produce a number of different heights. This arrangement can be provided by a two-piece tall core with a screw on replaceable end that can account for the numerous variations in height, which can account for varying thicknesses in tablets. The inner wall can be constructed of a desiccant entrained plastic.

**[0036]** Figures 11 and 12 show another embodiment in which concentric rings are formed onto the base of the container in a two shot molding process. Alternatively, the rings are formed in an overmolding process. The height of the rings is determined by a two-piece plastic core that has a replaceable end that has different ring depths machined into it. The rings can be formed of a desiccant-entrained plastic.

**[0037]** Figure 13 shows another embodiment in which a false bottom is positioned above the base of the container. A desiccant-containing sachet 53 is positioned in the space between the false bottom and the base. Throughbores 51 are positioned in the false bottom so that moisture can be absorbed by the desiccant. Alternatively, a screen is employed in lieu of the false bottom. The false bottom or screen may be constructed of a desiccant entrained plastic.

**[0038]** The embodiments of the present invention provide a one-piece vial assembly with an attached cap. When the vial assembly cap is opened, the cap is not misplaced. It is also contemplated that, by making the cap integral with container, the time the vial is left open by a user should be a shorter period of time when compared to a two-piece vial construction, such as a container with a screw-off cap. Consequently, ensuring that the cap is closed at all times, except when it is necessary

to have it open, is useful in maintaining product integrity of a moisture-sensitive product.

[0039] In yet another embodiment, the vial assembly of the present invention is provided with an "easy-to-close" cap design. That is, the vial assembly is specifically designed to be in one of only two states: (1) open and (2) completely closed. The closure arrangement is designed so that the cap cannot be partially closed or cross-threaded. If the cap does not seal properly, it should pop up. Also, in yet another embodiment, the cap is designed so it can be closed with one hand. Thus, the user should be able to close the cap from any position with respect to the hinge (front, side or back of vial assembly). In addition to the present application, pending U.S. patent application no. 09/386,702 describes this arrangement and is incorporated herein by reference.

[0040] It is further believed that, compared with stoppered vials, the embodiments of the present invention may require a lower opening force to open the cap of the vial assembly. In one example, the cap requires approximately 1/3 to 1/2 the force required to open a conventional stoppered vial. Pending U.S. patent application no. 09/386,702 describes this arrangement and is incorporated herein by reference.

[0041] In yet another embodiment, the vial assembly of the present invention are provided with a leak-proof and moisture tight seal. The vial assembly design, which includes closing the cap in the mold, ensures a leak proof and low moisture ingress seal. In one example, the vial assembly of the present invention has a moisture ingress rate of less than <250 µg/day. In another embodiment, this relatively low ingress rate, coupled with the desiccant entrained plastic within the vial assembly, ensure a managed and controlled environment for the times stored within the vial assembly.

[0042] In a further embodiment, the vial assembly of the present invention maintains seal performance after repeated lid openings and closings. For example, the seal maintains a low ingress rate after repeated lid openings/closings. In one specific example, the seal maintains its low moisture ingress performance after 50 cycles of lid openings and closings. U.S. Patent nos. 4,812,116, 4,807,425 and 5,723,085, as well as pending U.S. patent application no. 09/386,702, filed August 31, 1999, and European patent document no. EP 625 948, describe examples of embodiments of the sealing arrangement. These references are incorporated herein by reference.

[0043] In one embodiment, the vial assembly of the present invention includes a desiccant entrained plastic. In one example, the desiccant entrained plastic is located at or near the cap (e.g. the spring element may be made of the desiccant entrained plastic and/or interior of the spring element may contain the desiccant entrained plastic). In yet another example, the desiccant entrained plastic is a sleeve that surrounds the items stored and packaged within the vial assembly. The sleeve covers at least partially the interior of the vial (e.

g. surrounds the vial assembly interior with a thin-walled plastic so that the product contained within the vial assembly is surrounded by the desiccant sleeve). In another example of the use of vial, after the vial assembly is represented by opened and closed, the desiccant entrained plastic sleeve re-establishes the low relative humidity environment inside the vial assembly in a short period of time (e.g. in as low as less than about one minute).

[0044] The desiccant entrained plastic contains a desiccant such as silica gel or molecular sieve as the desiccant. Depending on the application, such as the application intended by the end user, molecular sieve or silica gel desiccant can be provided in the sleeve. For example, molecular sieve can be used for applications that require a low RH (e.g. less than <10% RH) maintained over the shelf life. In another example, silica gel can maintain a RH of 10-30% over a two year shelf life.

[0045] Suitable desiccant entrained plastic include these desiccant plastics disclosed in U.S. patent nos. 5,911,937, 6,214,255, 6,130,263, 6,080,350 and 6,174,952, 6,124,006, 6,221,446 and U.S. Serial No. 09/504,029, filed February 14, 2000. By varying the desiccant loading and channeling agent in the plastic formulation, the overall moisture capacity and uptake rate of the desiccant entrained plastic can be controlled. These references are incorporated herein by reference.

[0046] In another embodiment, in addition to providing an embodiments that exhibit moisture absorption properties, the plastic may be entrained with other absorbing, releasing or activation components. U.S. Patent nos. 6,174,952, 6,177,183, 6,194,079, 6,316,520, 6,124,006, 6,221,446 and U.S. Serial No. 09/504,029 describe these kinds of arrangements and are incorporated herein by reference.

[0047] In one embodiment, the vials may be manufactured by the process described in U.S. Patent Nos. 4,812,116 and 4,807,425 that are incorporated by reference herein. By closing the vial assembly lid inside the mold insures a clean, an aseptic environment inside the vial assembly may be maintained. Other examples of method of producing the vial include, but are not limited to, U.S. Patent No. 5,723,085 and 6,330,064 that are incorporated by reference herein.

[0048] In yet another embodiment, a child resistance feature may be incorporated into the vial assembly. An example of such an arrangement is disclosed in pending U.S. patent application no. 09/641,203, filed October 3, 2000, which is incorporated herein by reference.

[0049] In another embodiment, a tamper evidence feature that is molded into the vial assembly may be employed. An example is achieved with a two-position, breakaway tab that is disclosed in pending U.S. patent application no. 09/710,330, incorporated herein by reference. The tab is engaged during vial assembly filling, and the tab is ejected from the vial assembly when first opened by the user. This type tamper evidence feature is an alternative to shrink-wrapping the lid and container

body, which also may be used.

[0050] In a further embodiment, the features of the present invention may be manifested in a variety of vial assembly designs, including but not limited to designs having non-cylindrical vial assembly shapes.

[0051] Numerous modification and variations of the present invention are possible in light of the above discussion.

[0052] It will be appreciated that many modifications and other variations that will be appreciated by those skilled in the art within the intended scope of this invention without departing from the teachings, spirit and intended scope of the invention.

#### Claims

1. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of:

a container portion;  
a cap portion;  
a hinge joining the container portion and the cap portion;  
a spring element joined to an inner side of the cap portion; and  
a desiccant material retained by the spring element.

2. The container and cap assembly of claim 1 wherein the hinge is integral with the container portion and the cap portion.

3. The resealable container of claim 1 wherein the container is further comprised of a desiccant sleeve positioned within the container.

4. The resealable container of claim 1 wherein the spring element is comprised of a desiccant-entrained plastic.

5. The resealable container of claim 1 wherein the spring element retains a desiccant-containing sachet.

6. The resealable container of claim 1 wherein the container is further comprised of a tamper-proof seal.

7. The resealable container of claim 3 wherein the tamper-proof seal comprises:

a flexible and a detachable protrusion having a contact element and a break point positioned on an outer surface on the upper portion of the container, the tab of the cap having a first slot

and a second slot capable of housing the protrusion, the second slot having an interlocking device; wherein, when the container is in an empty stage, the protrusion is positioned within the first slot; and wherein, when the container is filled, the cap is closed upon the container and the protrusion is repositioned within the second slot, thereby allowing a contact element of the protrusion to engage the interlocking device to form a tamper-proof seal.

8. The resealable container of claim 1 wherein said cap is press-fit to said rim of said container during said closed position.

9. The resealable container of claim 1 wherein the container is provided with a flange having a protrusion with a u-shaped element, the protrusion further having a contact element and a break point, the tab having first slot in the tab of the cap, and the tab having a second slot provided with an interlocking device, wherein, when the container is empty, the contact element is situated in a first slot in the underside of the tab of the cap, and wherein, when the cap is placed upon the container, the protrusion is repositioned with the second slot on the tab, with the contact element of the protrusion engaging the interlocking device of the second slot to form a tamper-proof seal.

10. The container and cap assembly of claim 1 wherein effervescent tablets are packaged and retained in the container.

11. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of: a container having an upper portion and an outer surface, the container having a rim at the upper portion; a cap having a base with an outer periphery and a skirt extending perpendicularly and outwardly around the outer periphery of the base, a spring element joined to an inner side of the cap, a desiccant material retained by the spring element, the skirt having an inner wall, the inner wall having at least one recess, the cap having opposing ends, the cap including a thumb tab for facilitating the opening and closing of the container and a hinge joined to the cap and container, the thumb tab and the hinge being positioned on opposing ends of the cap and extending perpendicularly and outwardly from the skirt of the cap; and wherein, in a closed position, the skirt of the cap overlies the container and the rim of the container being situated within the recess of the inner wall of the skirt of the cap that results in a sealed container.

12. The container and cap assembly of claim 11 where-

in the hinge is integral with the container portion and the cap portion.

13. The resealable container of claim 11 wherein the container is further comprised of a desiccant sleeve positioned within the container.

14. The resealable container of claim 11 wherein the spring element is comprised of a desiccant-entrained plastic.

15. The resealable container of claim 11 wherein the spring element retains a desiccant-containing sachet.

16. The resealable container of claim 11 wherein the container is further comprised of a tamper-proof seal.

17. The resealable container of claim 11 wherein the tamper-proof seal comprises:

a detachable protrusion having a contact element and a break point positioned on an outer surface on the upper portion of the container, the tab of the cap having a first slot and a second slot capable of housing the protrusion, the second slot having an interlocking device; wherein, when the container is in an empty stage, the protrusion is positioned within the first slot; and wherein, when the container is filled, the cap is closed upon the container and the protrusion is repositioned within the second slot, thereby allowing a contact element of the protrusion to engage the interlocking device to form a tamper-proof seal.

18. The resealable container of claim 11 wherein said cap is press-fit to said rim of said container during said closed position.

19. The resealable container of claim 11 wherein the container is provided with a flange having a protrusion with a u-shaped element, the protrusion further having a contact element and a break point, the tab having first slot in the tab of the cap, and the tab having a second slot provided with an interlocking device, wherein, when the container is empty, the contact element is situated in a first slot in the underside of the tab of the cap, and wherein, when the cap is placed upon the container, the protrusion is repositioned with the second slot on the tab, with the contact element of the protrusion engaging the interlocking device of the second slot to form a tamper-proof seal.

20. The container and cap assembly of claim 11 wherein effervescent tablets are packaged and retained

in the container.

21. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of: a container portion having a sidewalls and bottom; a cap portion; a spring element joined to bottom of the container portion; and a desiccant material retained by the spring element.

22. The resealable container of claim 21 wherein the spring element is comprised of a desiccant-entrained plastic.

23. The resealable container of claim 21 wherein the spring element retains a desiccant-containing sachet.

24. The resealable container of claim 21 wherein the container is further comprised of a desiccant sleeve positioned within the container.

25. The resealable container of claim 21 wherein the container is further comprised of a tamper-proof seal.

26. The resealable container and cap assembly of claim 21 further comprised of a hinge joining the container portion and the cap portion.

27. The container and cap assembly of claim 21 wherein the hinge is integral with the container portion and the cap portion.

28. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of: a container portion having a sidewalls and bottom; a cap portion; a platform positioned proximate the base of the container portion; and a desiccant material retained by the platform.

29. The resealable container of claim 28 wherein the platform is a false bottom having throughbores.

30. The resealable container of claim 28 wherein the platform is a screen.

31. The resealable container of claim 28 wherein the platform is comprised of a desiccant-entrained plastic.

32. The resealable container of claim 28 wherein the platform retains a desiccant-containing sachet.

33. The resealable container of claim 28 wherein the container is further comprised of a desiccant sleeve



positioned within the container.

34. The resealable container of claim 28 wherein the container is further comprised of a tamper-proof seal. 5
35. The resealable container and cap assembly of claim 28 further comprised of a hinge joining the container portion and the cap portion. 10
36. The container and cap assembly of claim 28 wherein the hinge is integral with the container portion and the cap portion.
37. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of: a container portion having a sidewalls and bottom; a cap portion; an inner sidewall positioned above the base and providing a ledge on which an item can rest, a desiccant material retained by the inner sidewall. 15 20
38. A resealable container and cap assembly for packaging and retaining items that require packaging and retention in a substantially moisture-free environment, comprised of: 25
- a container portion;
  - a cap portion; 30
  - a hinge joining the container portion and the cap portion;
  - a spring element joined to an inner side of the cap portion; and
  - a desiccant sleeve positioned within the container. 35

40

45

50

55







Figure 1











Figure 7




Figure 8






Figure 9




Figure 10




Figure 11




Figure 12





Figure 13





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 03 25 2334

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	EP 1 118 552 A (CAPITOL VIAL INC) 25 July 2001 (2001-07-25)  * the whole document * ---	1-3, 6-13, 16-20, 24,26, 27,33, 35,36,38	B65D51/30 B65D81/26 B65D43/16
Y	EP 0 147 507 A (SANNER FRIEDR GMBH CO KG) 10 July 1985 (1985-07-10)  * the whole document * ---	1-3,6, 8-13,16, 18,20,38	
Y	GB 1 533 528 A (GEIGER A) 29 November 1978 (1978-11-29) * the whole document * ---	1,2,11, 12,38	
Y	DE 94 12 075 U (SANNER FRIEDR GMBH CO KG) 6 October 1994 (1994-10-06)  * the whole document * ---	1-3,6, 8-13,16, 18,20,38	
X	US 3 826 358 A (BUTLER A ET AL) 30 July 1974 (1974-07-30) * column 4, line 15 - line 25 * * column 4, line 53 - line 55; figures *	21,28,37	B65D A61J
Y		24,26, 27,33, 35,36	
A	EP 0 454 967 A (GAPLAST GMBH) 6 November 1991 (1991-11-06)  * abstract; figures * ---	1,3,11, 13,21, 24,28, 33,38	
-/--			
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>18 July 2003</b>	Examiner <b>Gino, C</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 92 (P04001)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 03 25 2334

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 5 813 564 A (LUO YI-WEN) 29 September 1998 (1998-09-29)  * abstract; figures * -----	1, 5, 11, 15, 21, 23, 28, 32	
Y, D	WO 01 44102 A (BELFANCE JOHN ; CAPITOL VIAL INC (US); SUPRANOWITZ RONALD (US)) 21 June 2001 (2001-06-21) * the whole document * -----	1, 6, 7, 11, 16, 17, 19	
A	US 5 147 054 A (PEHR HAROLD T) 15 September 1992 (1992-09-15)  * abstract; figures * -----	1, 6, 7, 11, 16, 17, 19	
A	US 4 809 874 A (PEHR HAROLD T) 7 March 1989 (1989-03-07)  * abstract; figures * -----	1, 6, 7, 11, 16, 17, 19	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>18 July 2003</b>	Examiner <b>Gino, C</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 2334

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-07-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1118552	A	25-07-2001	EP 1118552 A2	25-07-2001
			EP 1000873 A2	17-05-2000
			AT 198728 T	15-02-2001
			AU 5550196 A	07-11-1996
			BR 9608007 A	30-11-1999
			CA 2218559 A1	24-10-1996
			CN 1185139 A	17-06-1998
			CZ 9703315 A3	14-07-1999
			DE 69611608 D1	22-02-2001
			DE 69611608 T2	03-05-2001
			DK 824480 T3	23-04-2001
			EA 970327 A1	30-04-1998
			EE 9700238 A	15-04-1998
			EP 0824480 A1	25-02-1998
			ES 2154815 T3	16-04-2001
			GR 3035632 T3	29-06-2001
			HU 9900643 A2	28-06-1999
			JP 9012064 A	14-01-1997
			NO 974805 A	10-12-1997
			NZ 306829 A	19-12-1997
			PL 322946 A1	02-03-1998
			SK 143897 A3	08-07-1998
			US 6080350 A	27-06-2000
			US 6221446 B1	24-04-2001
			US 6124006 A	26-09-2000
			WO 9633108 A1	24-10-1996
			US 6214255 B1	10-04-2001
			US 6174952 B1	16-01-2001
			US 6194079 B1	27-02-2001
			US 6177183 B1	23-01-2001
			US 6316520 B1	13-11-2001
			US 6279736 B1	28-08-2001
			US 6486231 B1	26-11-2002
			US 5911937 A	15-06-1999
			US 2002103271 A1	01-08-2002
			US 6130263 A	10-10-2000
EP 0147507	A	10-07-1985	DE 3346928 A1	04-07-1985
			EP 0147507 A2	10-07-1985
GB 1533528	A	29-11-1978	DE 7607077 U1	08-07-1976
			CH 611851 A5	29-06-1979
			ES 232123 Y	01-08-1978
			FR 2343657 A1	07-10-1977
DE 9412075	U	06-10-1994	DE 9412075 U1	06-10-1994

EPO FORM P/039

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 03 25 2334

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-07-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 3826358	A	30-07-1974	CA	1002006 A1	21-12-1976
			GB	1372666 A	06-11-1974
EP 0454967	A	06-11-1991	DE	4013799 A1	31-10-1991
			DE	59107008 D1	18-01-1996
			EP	0454967 A2	06-11-1991
			ES	2082870 T3	01-04-1996
US 5813564	A	29-09-1998	NONE		
WO 0144102	A	21-06-2001	AU	4707301 A	25-06-2001
			EP	1233924 A2	28-08-2002
			WO	0144102 A2	21-06-2001
			US	2002088814 A1	11-07-2002
			US	6398067 B1	04-06-2002
US 5147054	A	15-09-1992	NONE		
US 4809874	A	07-03-1989	AU	622165 B2	02-04-1992
			AU	3280689 A	22-09-1989
			CA	1316844 C	27-04-1993
			DE	68922304 D1	24-05-1995
			DE	68922304 T2	11-01-1996
			EP	0401292 A1	12-12-1990
			JP	8029787 B	27-03-1996
			JP	3504116 T	12-09-1991
			WO	8908057 A1	08-09-1989

EPO FORM P0469

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82